

PhaseGuard ST 40-S

How to order?

1

2

3

4

5



- Communication
- LT: 0/4 ... 20 mA
- IO: 0/4 ... 20 mA
Modbus RTU
- Profibus DP
- Modbus RTU
- PoE – Power over Ethernet
Web-Server & Modbus-TCP

- XX
- LT
- IO
- PB
- PN
- PE

Photometer Product variants and sets				
PhaseGuard ST 40 – S2XX-0000.000 Turbidity measurement for phase separation				
With blanking plate				Without blanking plate
	30 m, 8-pin,1 plug 	20 m, 8-pin,1 plug 	10 m, 8-pin,1 plug 	
	123904	123903	123902	123767
		123906	123905	123768
123907				123769
123908				123770
123909				123771

PhaseGuard ST 40-H

How to order?

1

2

3

4

5



- Communication
- LT: 0/4 ... 20 mA
- IO: 0/4 ... 20 mA
Modbus RTU
- Profibus DP
- Modbus RTU
- PoE – Power over Ethernet
Web-Server & Modbus-TCP

- XX
- LT
- IO
- PB
- PN
- PE

Photometer Product variants and sets				
PhaseGuard ST 40 – H2XX-8000.000 Measurement of high turbidity for phase separation				
With blanking plate				Without blanking plate
	30 m, 8-pin,1 plug 	20 m, 8-pin,1 plug 	10 m, 8-pin,1 plug 	
	123868	123867	123866	123736
		123870	123869	123579
123871				123764
123872				123765
123873				123766